

## Barrie Scissor Lift License

Barrie Scissor Lift License - There is an inherent risk in operating a scissor lift, since with all types and kinds of powered work tools would need right handling to prevent accidents that could result in injuries or damage. Businesses must ensure that personnel utilizing this equipment have the necessary training.

Companies must not allow scissor lifts to be used by unqualified people. The scissor lift is designed to raise people to high levels. Failure to understand and completely abide by safety standard could lead to injuries for the users or damage to the lift.

For those who use scissor lifts, there is no legislation governing the utilization of fall protection. Nonetheless, manufacturers could recommend the use of fall protection and in several cases tying off in scissor lifts might be required by employer rules, job-specific risk assessments or local regulations.

Before using the equipment, the scissor-lift operator has to carry out a thorough check to be able to ensure the equipment is in good working condition. This is the operator's duty, even though the unit has already been in service that same day. The operator's instruction manual of the equipment contains a checklist for pre-operation.

Examples of what to look for when performing a pre-operation inspection consist of checking tire-inflation pressure, and checking ground controls and controls in the platform in order to make certain they are working. When retracting or extending the boom, look for delayed movement on the fly section which can indicate loose cables. Whilst operating the controls, make sure that the emergency stop switches are working. Operate functions against the machine's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters must automatically stop the unit before it moves into an unstable position, if they are working right. If they aren't, turn off the lift and make certain that it is fixed before it is used again.

Proper and safe operating procedures should be followed always. Levers should be operated with even, controlled pressure. A control lever must never be pushed from one position to the opposite position. The lever must be shifted to neutral, prior to stopping, and then proceeding in the desired direction. When released, levers and control switches must automatically return to the neutral position. Depress the foot switch before operating platform controls.