

## Barrie Loader Ticket

Barrie Loader Ticket - Gehl articulated loaders have been made to fit just about every condition. They provide optimal maneuverability and great traction thanks to a heavy-duty oscillating joint which offers forty five degree revolving angles left and right, with 10 degrees of oscillating in either direction. Access is fixed to confined and tight spaces by narrow engine widths. Most skid-steer loaders with comparable operating capacities are unable to compete. The tires and bucket on the Gehl equipment follow a constant turn radius too. This means the rear tires of the loader follow the course of the front tires.

The articulated loaders features hydraulic precision and power that come together with all Gehl equipment. Bucket float and lift arm features allow these machines to carry out light scraping and rearward leveling actions. Flat-face couplers, together with the two easily accessible auxiliary hydraulic lines power many tools and make changing the accessories an easy task to complete.

The articulated loaders constructed by Gehl have hoist arms which are uniquely designed for a fast time cycle, to maximize strength and for great visibility. The linkage pattern is specialized to allow for mechanized self-leveling action in downward and upward directions. It could even easily perform exceptional bucket dump angles at the top and mid ranges of the hoist path along with offering excellent forward reach. Models 340 and 140 have parallel kind linkage and the model 540 has "Z" bar kind linkage. These linkage patterns offer great bucket breakout forces from 2433lbs on the 140 model to ten thousand seven hundred forty nine pounds on the 540 model.

Gehl articulated loaders are known world-wide for their supreme ergonomics, unsurpassed visibility and ease of operation. The 340 and 540 machines have a total cab enclosure preference obtainable. This offers better comfort and safety for the person operating it. Secure operation and 360 degree visibility is sustained by positioning the person operating it higher than the load to guarantee an excellent viewpoint of the accessory. An inching pedal allows the operator to alter ground speed whilst maintaining a fixed engine speed. This particular feature allows the person operating it to optimally run attachments while making sure precise machine velocity control. A multi-function joystick controls the bucket, travel direction, float, differential lock and auxiliary hydraulic functions and the lift arm.